

节能型本地温控器型号及功能配置清单

产品型号	应用			功能							输入	输出		电源
	二管制	四管制	两线电动阀	LCD液晶显示	本地控制	面板锁定	高低温保护*	断电记忆	温控范围可调*	节能模式	外置感应器*	开闭量输出	负载容量	220VAC
KA/P-085-2R0108	●		●	●	●			●			●	●	3A	●
KA/P-085-2R0208	●		●	●	●		●	●		●	●	●	3A	●
KA/P-085-2R0308	●		●	●	●	●	●	●	●	●	●	●	3A	●
KA/P-085-2N0108	●		●	●	●			●				●	3A	●
KA/P-085-2N0208	●		●	●	●		●	●		●		●	3A	●
KA/P-085-2N0308	●		●	●	●	●	●	●	●	●		●	3A	●
KA/P-085-2N0408	●		●	●	●	●		●	●			●	5A	●
KA/P-085-2R0408	●		●	●	●	●		●	●		●	●	5A	●
KA/P-085-2R0508	●		●	●	●		●	●	●	●	●	●	3A	●
KA/P-085-2N0508	●		●	●	●		●	●	●	●		●	3A	●
KA/P-085-4R0108		●	●	●	●			●			●	●	3A	●
KA/P-085-4R0208		●	●	●	●		●	●		●	●	●	3A	●
KA/P-085-4R0308		●	●	●	●	●	●	●	●	●	●	●	3A	●
KA/P-085-4N0108		●	●	●	●			●				●	3A	●
KA/P-085-4N0208		●	●	●	●		●	●		●		●	3A	●
KA/P-085-4N0308		●	●	●	●	●	●	●	●	●		●	3A	●
KA/P-085-4N0408		●	●	●	●	●		●	●			●	5A	●
KA/P-085-4R0408		●	●	●	●	●		●	●		●	●	5A	●
KA/P-085-4R0508		●	●	●	●		●	●	●	●	●	●	3A	●
KA/P-085-4N0508		●	●	●	●		●	●	●	●		●	3A	●

备注:

- 1.科易达节能型温控器所有型号产品都可通过三线制水阀适配器（可选配件）实现对三线制水阀的控制。
- 2."高低温保护"功能是指当温度低于5℃或高于40℃时，温控器能自动启动防止室温过高或过低造成所造成的室内设施的损坏。
- 3."温控范围可调"功能是指，温控器的制冷、制热的温度控制范围，可根据业主要求进行上下限调整。
- 4."外置感应器输入"功能是指，温控器具备与无线窗磁感应器；无线人体感应器联动控制空调运行模式的功能。（无线窗磁感应器；无线人体感应器可选配件）